

TOP SECRET



NRO REVIEW COMPLETED

COR 1064  
Copy 2 of 5 copies  
25 January 1961

25X1A

MEMORANDUM FOR: Mr. John Parengosky, DPD-DD/P  
SUBJECT: Trip Report - [redacted]

1. Purpose: To attend a conference at Itek Corporation on the status of the C111 program.

2. General:

a. C111 Status - The April date previously established appears to still be possible. The only real cause for concern was the lack of decision on which clock to use. The decision on using the "A" clock had not been communicated to Itek in time for the meeting. The Itek group knew almost nothing about the "A" clock and were concerned with mounting problems, etc., if the "A" clock were chosen.

b. Characteristics of the Boston Clock

- (1) Accuracy - 1/200th of a second. This is accomplished by coupling to timing "pips" (200 per second), reading clock to tenths of seconds, and interpolating by counting timing "pips".
- (2) Reliability - No operational experience, but tests have shown very high reliability.
- (3) Reset Capability - Can be reset in orbit if command channel can be made available.
- (4) Drift -  $1 \times 10^{-6}$  (same as C1).
- (5) Readout - Clock or digital.

c. C111 Characteristics:

- (1) The following camera characteristics differ from C1 and are of interest to TIS for computer program changes and exploitation planning.

This document contains information referring to TOP SECRET

TOP SECRET

- (2) There are 200 timing "pips" per second instead of 160 "pips" per second on the C<sup>1</sup>.
- (3) The lens system rotates continuously and the chimney oscillates.
- (4) The sweep direction is opposite to that in the C<sup>1</sup>. (C<sup>III</sup> sweeps from left to right in the camera.)
- (5) Lens #1 resolves 475 lines per millimeter on the bench and 150 lines per millimeter on S.O. 1221 film.
- (6) Sweep time is approximately 14% slower.
- (7) A lens - "flattener" - is located right at the image plane. It has its own cam for IMC.

25X1A

d. IMC Problems - Some time was spent with [redacted] of Itek discussing IMC on C<sup>1</sup> and C<sup>III</sup>. Previously a great deal of confusion existed on whether IMC or FMC was provided. Most of the data available indicated FMC, though IMC seemed to be the most plausible. The discussion resolved the problem - IMC and not FMC is provided on C<sup>1</sup> and C<sup>III</sup>.

25X1A

e. LMSD Computer Services - [redacted] talked about the possibility of LMSD providing PIC computer services. This seems to be a very interesting possibility. LMSD not only has the equipment and mathematicians, astronomers, etc., but also has people already cleared operationally and familiar with photogrammetric analysis. The undersigned recommends LMSD be contacted to further this discussion.

f. Camera Relative Orientation - It is believed that the present system of camera orientation accomplished on the West Coast is useful only to determine the orientation between the vehicle and the camera system and does not determine the relative orientation between the three cameras. The orientation procedure now accomplished by LMSD should be evaluated and the requirement for the vehicle/camera orientation should be reviewed.

25X1A

PIC must communicate with DPD-DD/P concerning the continued requirement for camera logs for the C<sup>III</sup> program. This log must include depression angles of the horizon cameras, as the present C<sup>1</sup> log does.

25X1A

FIC/TISD/TIB [redacted] jem(2845) [redacted]

25X1A

Original - Addressee 3 - Chief, TISD/PIC / 5 - RI Files  
2 - [redacted] 4 - Chief, TISD/TIB/PIC